



CLAMP SIZE	DIMENSIONS (mm)			
	A	B	L	LV
1"	50.5	22.1	207	98
1"1/2	50.5	34.5	207	98
2"	64	47.5	226	98
2"1/2	77.4	60.2	226	85
3"	91	72.8	226	85
4"	119	97.4	226	85

Customized lengths available upon request.

CLAMP SIZE	Standard		w/ Safety Grill	
	Working Pressure	Bursting Pressure	Working Pressure	Bursting Pressure
1"	116	464	174	696
1"1/2	87	363	174	696
2"	73	319	145	682
2"1/2	73	319	145	580
3"	73	290	131	522
4"	58	232	58	232

Pressure rating above refer to ambient temperatures. We suggest a reduction of 20% for the above pressures for every 20 degree Celsius above ambient temperature. For diameters 3" and 4", we recommend a safety grill from 60 Degrees F and 30 psi.

2	NON-GLASS TUBE	1	FLUORED THERMOPLASTIC		
1	SANITARY CLAMP END	2	316L STAINLESS STEEL		
ITEM	DESCRIPTION	QTY	MATERIAL	PART NO.	NOTES
ITEM	-				
COMM./INTERNA	-				
COMM./CLIENT	-				
In the interest of development and improvement of the product, we reserve the right to change the specifications.					
GROUP:		DIMENSIONS			
Non-Glass Flow Indicators		DATE	23-05-03	SCALE	1:1
Description:		FORMAT	LTR		
1" - 4" Non-Glass Flow Indicator		Designer	JB		
		Control			
		Design No.	-		
		REV.			

This drawing is the property of SPC, Inc. and is transmitted in confidence. The reproduction, use, or disclosure, in whole or part, of the design contained herein is prohibited without the written consent of SPC, Inc.

Sanitary Process Components, Inc.
Tel: 407-650-8988 Fax: 407-650-8944