



CLAMP SIZE	DIMENSIONS (mm)			
	A	B	L	LV
1"	50.5	22.1	207	98
1 1/2"	50.5	34.5	207	98
2"	64	47.5	226	98
2 1/2"	77.4	60.2	226	85
3"	91	72.8	226	85
4"	119	97.4	226	85

Customized lengths available upon request.

CLAMP SIZE	Pressure Rating (in psf)			
	Standard Working Pressure	Bursting Pressure	V/ Safety Working Pressure	CR1 Bursting Pressure
1"	116	464	174	696
1 1/2"	87	363	174	696
2"	73	319	145	682
2 1/2"	73	319	145	580
3"	73	290	131	522
4"	58	232	58	232

Pressure rating above refer to ambient temperature. We suggest a reduction of 20% for the above pressures for every 20 degrees Celsius above ambient temperature. For diameters 3" and 4", we recommend a safety gift from 80 Degrees F and 50 psi.

ITEM	DESCRIPTION	QTY	MATERIAL	PART NO.	NOTES
2	NON-GLASS TUBE	1	FLUORED THERMOPLASTIC		
1	SANITARY CLAMP END	2	316L STAINLESS STEEL		

COMM.CLIENT	—	MATERIAL	DIMENSIONS	
CDM/INTERNA	—	General Tolerances:	DATE	23-05-03
		SIND A 30: 20.10 ; MAGGIORI A 30: 10.20	FORMAT	LTR
			Designer	JB
			Control	
			Design No.	—
			REV.	

This drawing is the property of SPC, Inc. and is transmitted in confidence. The reproduction, use, or disclosure, in whole or part, of the design contained herein is prohibited without the written consent of SPC, Inc.

Sanitary Process Components, Inc.
 Tel: 407-650-8988 Fax: 407-650-8944